




SADL Bracket A2 for Trimdeck Roof

Assembly








Rail running perpendicular to roof rib



Rail running parallel to roof rib



Rail running perpendicular to roof rib

With Cross Connector Clamp

Component



With Tin Interface

SADL Bracket A2
Part No.: ER-I-65 (bar code: 10-002-00663)

Technical Specification

| Application | Lysaght Trimdek Trapezoidal Roof sheet penetration |
|----------------------------|---|
| Fasteners Specification | 4 x Buildex M6-11 x 25 (12 gauge, 6.0 mm, 11 TPI, 25 mm long) Hex Head Teks with 16 mm Bonded Washer, C4 rated; 1 x Hexagon socket head bolt M8*20 |
| EPDM | Pre-fitted (2 x 2mm thickness) |
| Dimensions | L70mm*W60 mm*H36.5mm |
| Packaging | 40 units per pack, 4 packs (160 units) per carton |
| Packaging Dimension | L397*W267*H345mm (carton dimension) |
| Weight | 0.115 Kg; 20 Kg (carton weight) |
| Material | Main Structure: AL6005-T5 Self-drilling Screws: Carbon Steel SAE 1022 Bolt/washers: SUS 304 Rubber Pads: EPDM |
| Color | Silver (Anodized, no less than 10 μm, excluding machined surfaces) |
| Standard | AS NZS1170.2 |

