

Component

						
Tin Interface 8 Units	Inter Clamp 30 mm 6 Units	End Clamp 30 mm 4 Units	Elite Rail Splice 2 Units	EZ-GL-ST 2 Units	EZ-CC-PV/2 8 pcs	EZ-GC-ST 6 Units
PV-ezRack, SolarRoof Kit of Tin Roof for 4 Panels with 30 mm Clamps, Partially Black Anodized Part No.: K-SR-05/4/30/BP (bar code: 21-136-00046)						

						
Tin Interface 14 Units	Inter Clamp 30 mm 14 Units	End Clamp 30 mm 4 Units	Elite Rail Splice 2 Units	EZ-GL-ST 2 Units	EZ-CC-PV/2 16 pcs	EZ-GC-ST 14 Units
PV-ezRack, SolarRoof Kit of Tin Roof for 8 Panels with 30 mm Clamps, Partially Black Anodized Part No.: K-SR-05/8/30/BP (bar code: 21-136-00047)						

						
ER-I-01/CS 8 Units	Inter Clamp 30 mm 6 Units	End Clamp 30 mm 4 Units	Elite Rail Splice 2 Units	EZ-GL-ST 2 Units	EZ-CC-PV/2 8 pcs	EZ-GC-ST 6 Units
PV-ezRack, SolarRoof Kit of Tile Roof for 4 Panels with 30 mm Clamps, Partially Black Anodized Part No.: K-SR-01/4/30/BP (bar code: 21-137-00031)						

						
ER-I-01/CS 14 Units	Inter Clamp 30 mm 14 Units	End Clamp 30 mm 4 Units	Elite Rail Splice 2 Units	EZ-GL-ST 2 Units	EZ-CC-PV/2 16 pcs	EZ-GC-ST 14 Units
PV-ezRack, SolarRoof Kit of Tile Roof for 8 Panels with 30 mm Clamps, Partially Black Anodized Part No.: K-SR-01/8/30/BP (bar code: 21-137-00032)						

Technical Specification

Roof type	K-SR-05/4/30/BP & K-SR-05/8/30/BP: Tin Roof K-SR-01/4/30/BP & K-SR-01/8/30/BP: Tile Roof
Purlin requirement	Metal or Timber purlin
Screw specification	K-SR-05/4/30/BP & K-SR-05/8/30/BP: Buildex 14-11 x 70 (14 gauge, 6.3 mm, 11 TPI, 70 mm long) Hex Head Zips Screw K-SR-01/4/30/BP & K-SR-01/8/30/BP: Buildex 14-10 x 65 (14 gauge, 6.3 mm, 10 TPI, 65 mm long) Hex Head Zips screw
PV panel dimension	Framed PV Modules of 30 mm in height
Weight	K-SR-05/4/30/BP: 1.935 Kg K-SR-05/8/30/BP: 3.260 Kg K-SR-01/4/30/BP: 5.767 Kg K-SR-01/8/30/BP: 9.966 Kg
Packaging	K-SR-05/4/30/BP: 1 unit per pack ;8 packs (8 units) per carton K-SR-05/8/30/BP: 1 unit per pack ;4 packs (4 units) per carton K-SR-01/4/30/BP: 1 unit per pack ;2 packs (2 units) per carton K-SR-01/8/30/BP: 1 unit per pack ;1 packs (1 units) per carton
Material	Tin Interface : AL6005-T5 Tile Interface : Q345B Cable Clip : SUS304(3/4H) Grounding Lug : SUS316 & AL6005-T5 Clamp and Splice : AL6005-T5
Finish and Color	Black Anodized (Fabricated Surfaces are Mill Finish) Silver Hot Dip Galvanized (Tile Interface)
Standard	AS NZS1170.2-2021