





















Kit for SolarRoof with ECO-Rails with Akashi Clamp 30-46mm

Component

				
ER-I-05 10 Units	C-U/30/46-G 10 Units	EZ-CC-PV/2 8 Units	EZ-GL-ST 2 Units	ER-SP-ECO 2 Units
Kit for SolarRoof Tin Roof with ECO-Rails for 4 panels with Akashi Clamp 30-46mm Part No.: K-ECO/05/4/U (bar code: 13-12015-173)				

				
ER-I-05 16 Units	C-U/30/46-G 18 Units	EZ-CC-PV/2 16 Units	EZ-GL-ST 2 Units	ER-SP-ECO 2 Units
Kit for SolarRoof Tin Roof with ECO-Rails for 8 panels with Akashi Clamp 30-46mm Part No.: K-ECO/05/8/U (bar code: 13-12015-172)				

				
ER-I-01 10 Units	C-U/30/46-G 10 Units	EZ-CC-PV/2 8 Units	EZ-GL-ST 2 Units	ER-SP-ECO 2 Units
Kit for SolarRoof Tile roof with ECO-Rails for 4 panels with Akashi Clamp 30-46mm Part No.: K-ECO/01/4/U (bar code: 13-12010-055)				

				
ER-I-01 18 Units	C-U/30/46-G 18 Units	EZ-CC-PV/2 16 Units	EZ-GL-ST 2 Units	ER-SP-ECO 2 Units
Kit for SolarRoof Tile roof with ECO-Rails for 8 panels with Akashi Clamp 30-46mm Part No.: K-ECO/01/8/U (bar code: 13-12010-053)				

Technical Specification

Application	K-ECO/05/4/U & K-ECO/05/8/U: Tin Roof K-ECO/01/4/U & K-ECO/01/8/U: Tile Roof
Purlin Requirement	K-ECO/05/4/U & K-ECO/05/8/U: Metal or Timber purlin K-ECO/01/4/U & K-ECO/01/8/U: Timber purlin
Screw Specification	K-ECO/05/4/U & K-ECO/05/8/U: Buildex 14-11 x 70 (14 gauge, 6.3 mm, 11 TPI, 70 mm long) Hex Head Zips Screw K-ECO/01/4/U & K-ECO/01/8/U: Buildex 14-10 x 65 (14 gauge, 6.3 mm, 10 TPI, 65 mm long) Hex Head Zips screw
PV panel dimension	Framed PV Modules of 30-46 mm in height
Weight	K-ECO/05/4/U: 2.650 Kg K-ECO/05/8/U: 4.062 Kg K-ECO/01/4/U : 7.359 Kg K-ECO/01/8/U : 12.799 Kg
Packaging	K-ECO/05/4/U: 1 unit per pack; 4 packs (4 units) per carton K-ECO/05/8/U: 1 unit per pack; 4 packs (4 units) per carton K-ECO/01/4/U: 1 unit per pack; 2 packs (2 units) per carton K-ECO/01/8/U: 1 unit per pack; 1 packs (1 units) per carton
Material	Tin Interface: AL6005-T5 Tile Interface: SUS304 Cable Clip: SUS304(3/4H) Grounding Lug: Hpb59-1&AL6005-T5 Clamp and Splice: AL6005-T5
Standard	AS NZS1170.2-2021