

## Tin Interface A with ezClick Connection

## Component



Tin Interface A with ezClick Connection, Ponte Screw 6.3x70 C3, Black Anodized Part No.: ER-I-05A/EZC/BA (bar code: 13-12015-201) Tin Interface A with ezClick Connection, Ponte Screw 6.3x70 C5, Black Anodized Part No.: ER-I-05A/EZC/C5/BA (bar code: 10-001-00902)

## **Technical Specification**

Application	Tin Roof (up to Category 5)
Purlin requirement	Metal or Timber purlin
Screw specification	Buildex 14-11 x 70 (14 gauge, 6.3mm, 11TPI, 70mm long) screw with 16mm Aluminum Bonded Washer
EPDM	Pre-fitted (2mm thickness)
Packaging	24 units per pack; 4 packs (96 units) per carton
Dimensions	L40mm*W38mm*H84mm L395mm*W260mm*H330mm (carton)
Weight	0.147 kg 15.4 kg (carton)
Material	Main Structure: AL6005-T5 Bolts/washers/nuts: SUS 304 Rubber Pad: EPDM ER-I-05A/EZC/BA Screw: Carbon Steel SAE1022 with Climaseal 3 finish ER-I-05A/EZC/C5/BA Screw: Carbon Steel SAE1022 with Climaseal 5 finish
Color	Black (black anodised)
Standard	AS NZS1170.2-2021





