











SolarRoof Kits for 6 panels with Akashi Clamp 30-46mm

Component

				
ER-I-05 12 Units	C-U/30/46-G 14 Units	EZ-CC-PV/2 12 Units	EZ-GL-AT 2 Units	ER-SP-ELT 2 Units
PV-ezRack, SolarRoof Kit of Tin Roof for 6 panels with Akashi Clamp 30-46 mm Part No.: K-SR-05/6/U (bar code: 21-136-00050)				

				
ER-I-01 12 Units	C-U/30/46-G 14 Units	EZ-CC-PV/2 12 Units	EZ-GL-AT 2 Units	ER-SP-ELT 2 Units
PV-ezRack, SolarRoof Kit of Tile Roof for 6 panels with Akashi Clamp 30-46 mm Part No.: K-SR-01/6/U (bar code: 21-137-00037)				

Technical Specification

Application	K-SR-05/6/U: Tin Roof K-SR-01/6/U : Tile Roof
Purlin Requirement	K-SR-05/6/U: Metal or Timber purlin K-SR-01/6/U : Timber purlin
Screw Specification	K-SR-05/6/U: Buildex 14-11 x 70 (14 gauge, 6.3 mm, 11 TPI, 70 mm long) Hex Head Zips Screw K-SR-01/6/U : Buildex 14-10 x 65 (14 gauge, 6.3 mm, 10 TPI, 65 mm long) Hex Head Zips Screw
PV panel dimension	Framed PV Modules of 30-46 mm in height
Weight	K-SR-05/6/U: 2.991 Kg K-SR-01/6/U : 8.631 Kg
Packaging	K-SR-05/6/U: 1 unit per pack; 4 packs (4 units) per carton K-SR-01/6/U : 1 unit per pack; 2 packs (2 units) per carton
Material	Tin Interface: AL6005-T5 Tile Interface: SUS304 Cable Clip: SUS304(3/4H) Grounding Lug: SUS316 & AL6005-T5 Clamp and Splice: AL6005-T5
Standard	AS NZS1170.2-2021